




Shandong Xiangyue bearing Trading Co....



NCF2930V Bearing 2D drawings and 3D CAD models

5.906 Inch | 150 Millimeter x 8.268 Inch | 210 Millimeter x 1.417 Inch | 36 Millimeter Timken NCF2930V Cylindrical Roller Bearing

Bearing No. NCF2930V

| | |
|---------------------------|---|
| Category | Cylindrical Roller Bearings |
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 3.765 |
| EAN | 0053893773117 |
| Product Group | B04144 |
| Bore Profile | Straight |
| Cage Material | None |
| Precision Class | RBEC 1 ISO P0 |
| Number of Rows of Rollers | Single Row |
| Separable | No |
| Rolling Element | Cylindrical Roller Bearing |
| Profile | Complete with Outer and Inner Ring |
| Snap Ring | No |
| Internal Clearance | C0-Medium |
| Retainer | No |
| Relubricatable | Yes |
| Inch - Metric | Metric |
| Other Features | Full Complement 2 Rib Inner Ring 1 Rib Outer Ring with Retaining Ring |
| Long Description | 150MM Bore; Straight Bore Profile; 210MM Outside Diameter; 36MM Width; |



Shandong Xiangyue bearing Trading Co....

| | |
|--------------------------------|---|
| | RBEC 1 ISO P0; Single Row; Not Separable; No Snap Ring; Relubricatable; C0-Medium Internal Clearance; No Retainer |
| Category | Cylindrical Roller Bearings |
| UNSPSC | 31171547 |
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| Manufacturer URL | http://www.timken.com |
| Manufacturer Item Number | NCF2930V |
| Weight / LBS | 8.3 |
| d | 5.906 Inch 150 Millimeter |
| D | 8.268 Inch 210 Millimeter |
| B | 1.417 Inch 36 Millimeter |
| Bore d | 150 mm |
| O.D. D | 210.000 mm |
| Width B | 36.000 mm |
| DUR/DOR F/E | 196.400 mm |
| Static Load Rating C_o | 506 kN |
| Dynamic Load Rating C_1^1 | 328 kN |
| Dimension S^2 | 2.20 mm |
| Geometry Factor C_g^3 | 0.1280 |
| Thermal Speed Ratings - Oil | 1010 rpm |
| Thermal Speed Ratings - Grease | 840 rpm |
| Weight | 8.3 lb |
| Chamfer r_{smin} | 2.00 mm |
| Chamfer r_{1smin}^4 | 1.1 mm |
| Backing Shaft Diameter d_s | 162.4 mm |
| Backing Housing Diameter D_s | 200.5 mm |