



NTN 51130 Thrust Spherical Roller Bearing

Bearing No. 51130

51130 Bearing 2D drawings and 3D CAD models

Size	150x190x31 mm
Bore Diameter	150 mm
Outer Diameter	190 mm
Width	31 mm
d	150 mm
D	190 mm
T	31 mm
d1	188 mm
r min.	1 mm
D1	152 mm
da min.	174 mm
Da max.	166 mm
ra max.	1 mm
Weight	2 Kg
Basic dynamic load rating (C)	109 kN
Basic static load rating (C0)	400 kN
(Grease) Lubrication Speed	1 200 r/min
Category	Thrust Ball Bearing
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.932
EAN	4547359306255
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes



Shandong Xiangyue bearing Trading Co....

Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row With Flat Seat
Long Description	150MM Bore 1; 152MM Bore 2; 190MM Outside Diameter; 31MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; ABEC 1 ISO P0 Precision
Inch - Metric	Metric
Category	Thrust Ball Bearings
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	51130
Weight / LBS	4.40925
Bore 1	5.906 Inch 150 Millimeter
Bore 2	5.984 Inch 152 Millimeter
Outside Diameter	7.48 Inch 190 Millimeter
Height	1.22 Inch 31 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
bore diameter:	150 mm
dynamic load capacity:	109000 N
outside diameter:	188 mm
operating temperature range:	-40 to 120 ° C



Shandong Xiangyue bearing Trading Co....

overall width:	31 mm
maximum rpm:	1800 rpm
thrust bearing type:	Single-Direction
bearing material:	High Carbon Chrome Steel
outside diameter design:	Straight
cage material:	Steel
separable or banded:	Separable
fillet radius:	1 mm
precision rating:	ISO Class 0
series:	511
static load capacity:	400000 N
manufacturer product page:	Click here